


FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or C14
- Power: 120-150W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 167*65*37.5mm
- Application: Consumer electronics, Telecom and office equipment



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

120W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-1201000-S12	100-240VAC	120W	12V	10.0A	C8, C6, C14
SW-1500800-S12	100-240VAC	120W	15V	8.0A	C8, C6, C14
SW-1900630-S12	100-240VAC	120W	19V	6.3A	C8, C6, C14
SW-2400500-S12	100-240VAC	120W	24V	5.0A	C8, C6, C14
SW-4800250-S12	100-240VAC	120W	48V	2.5A	C8, C6, C14

150W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-1501000-S12	100-240VAC	150W	15V	10.0A	C8, C6, C14
SW-1900780-S12	100-240VAC	150W	19V	7.8A	C8, C6, C14
SW-2400625-S12	100-240VAC	150W	24V	6.25A	C8, C6, C14
SW-3600416-S12	100-240VAC	150W	36V	4.16A	C8, C6, C14
SW-4800310-S12	100-240VAC	150W	48V	3.1A	C8, C6, C14

Mechanical Diagram:

	1	2	3	4	5	6	7	8	9	10	11	12	
A	REVISION												
	ISSUE	ZONE	DESCRIPTION	DATE	REVISER								A
B													B
C													C
D													D
E													E
F													F
G													G
H													H
I													I

STARWELL TECH CO.,LTD	DESIGN	CHECKED	APPROVED	UNIT	mm
				SIZE	A4
				REV.	A
	MODEL NO.	PART NO.	PART NAME	MATERIAL	DATE
			外观图		